SealTOUGH XE400 Films

HEAVYWEIGHT PERFORMANCE. LIGHTWEIGHT PACKAGE.



SealTOUGH™ XE400 clear, biaxially oriented films from Jindal Films provide 5,000g / 25mm of seal strength and outstanding clarity. The orientation process gives SealTOUGH improved stiffness, modulus and puncture resistance with less elongation. This enables significant down-gauging when compared to traditional blown PE sealant films.

SealTOUGH is available in four gauges: 18, 23, 30, and 40µm. Featuring a treated skin on one side, SealTOUGH is ideal for extrusion and adhesive lamination. The low-MST sealant skin on the other side provides superior seal strength and integrity.

SealTOUGH can be used in a number of formats, including VFFS, HFFS, overwrap, bags, and pouches.



SealTOUGH is ideal for replacing blown PE sealants

CLEAR!

Improved haze for enhanced product visibility

LIGHT!

Gauge reduction means lighter packages, cost reductions and sustainability benefits

STRONG!

Orientation provides higher tensile strength, improved modulus and outstanding puncture and impact resistance








SealTOUGH Property Comparisons

Delivering the Best of Both Worlds



- Enables down-gauging when replacing a blown PE sealant web.
- Provides outstanding clarity and directional tear properties, similar to OPP film.
- Reduced elongation and improved tensile strength provide better processing in converting and packaging.
- Provides outstanding seal strength and hermeticity, similar to PE films.
- Provides improved impact resistance versus PE. Property enhancement is even greater in freezing conditions.

Clearly Stronger



Improve performance with 40% down-gauge

Tensile Strength: 3-fold improvement

Modulus: 2-fold improvement

Elongation: 50% less

Puncture Resistance: > 2-fold improvement

Impact Resistance: 2-fold improvement

Clarity (Haze): 2-fold improvement

Count on Jindal Films

If you're looking to develop innovative flexible packaging solutions, try SealTOUGH films from Jindal Films. Contact us for more information and details about SealTOUGH XE400 film.

www.jindalfilms.com

EU +352 45 102 22 11 | US +1 800 231 6577 | CN +86 212 4261837 | info@jindalfilms.com

© 2016 Jindal Films, the Jindal Films logo, and other product or service names used herein are trademarks of Jindal Films, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without Jindal Films, prior written authorization. To the extent Jindal Films authorizes distributing, displaying and/or-copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to, or reproduce it in whole or in part on, a website. Jindal Films does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date complied, but we do not represent, warrant, or otherwise guarantee the accuracy, reliability, or ompleteness of this information; nor do we warrant, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, or suitability of the products, materials or processer described. The user is solely responsible for all determinations regarding any use of material or product and any process in its tertipories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a regult of, or related to, anyone using or relying on any of the information in this document. This document is not an endorsement of any non-dindal Films product or process, and we expressly disclaim any contrary implication. The terms west out, "Jundal Films" and "Jindal" are each used for convenience, and may include Films Americas LLC, Jindal Films Americas LLC, Films Europe S.A.R.L. or any companies affiliated with them in the production and safe of filmy products. There are a nu