

Improved barrier and machinability with Metallyte™ OPP film

Metallyte™ 40MM658 is a metallized cavitated white opaque polypropylene film, coated on metal.

FILM TYPE

Metallyte™ 40MM658 white, coated metallized OPP film

FORMAT

Horizontal form fill seal (HFFS) flowpack

MARKET SEGMENT

Biscuits & Bakery - Sweet Biscuits

APPLICATION

“Tosta Rica Choco Guay” biscuits from Adam Foods Cuétara

BRAND OWNER CHALLENGE

Barrier and machine performance



“Tosta Rica ChocoGuay” Chocolate biscuits
from Adam Foods Cuétara

Solution

- Metallyte™ 40MM658 film was chosen for its excellent barrier, allowing optimum protection for sensitive chocolate filled crispy biscuits, combined with efficient packaging performance on high speed HFFS machines
- Combination of high barrier metallization and over-coating technology provides a robust solution with a mono-web film
- Mono-web barrier film allows good balance of properties without requiring a multi-material lamination



Contact your Jindal Films representative for more information
www.jindalfilms.com - info@jindalfilms.com

Features

- Monoweb barrier metallized sealant solution
- Very low sealing temperature with VLTS coating
- Ease of converting on the coated metallized side
- Good seal integrity with cavitated base film

Benefits

- Outstanding protection for 12 month shelf-life
- Excellent visual appearance for good brand recognition
- Very good performance on HFFS packaging machines

Jindal
Films

© 2018 Jindal Films. Jindal Films, Jindal Films, the Jindal Films' logo, and other product or service names used herein are trademarks of Jindal Films, unless indicated otherwise. You may not upload, display, publish, license, post, point to, frame, transmit or distribute either this document or its information, whether in whole or in part, without Jindal Films' prior written authorization. To the extent Jindal Films provides prior written authorization, the user may use the document or its information only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. Any data included herein may be based upon: analyses of representative samples and not the actual product shipped, typical values, or otherwise. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We base the information on data believed to be reliable, but we do not represent, warrant, or otherwise guarantee the accuracy, reliability, or completeness of this information; nor do we warrant, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, or suitability of the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of, or related to, anyone using or relying on any of the information in this document. This document is not an endorsement of any non-Jindal Films' product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "Jindal Films" and "Jindal" are each used for convenience, and may include Films Americas LLO, Jindal Films Americas LLO, Films Europe S.à.r.l., Jindal Films Virton SPRL, Jindal Films India Ltd., or any companies affiliated with them in the production and sale of film products. There are a number of such affiliated companies, some with names including "Jindal" or "Films" and some not. Neither these terms and conditions, nor anything else in this document, is intended to override or supersede the legal separateness of those affiliated companies and responsibility for local action and accountability remains with them.