

Enhanced handling resistance through Metallyte™ OPP film

Metallyte™ 18MM883 film is an ultra-high barrier,
metallized polypropylene film.

FILM TYPE

Metallyte™ 18MM883 metallized OPP film

FORMAT

Four-side-sealed flat pouches

MARKET SEGMENT

Dry Foods

APPLICATION

Dehydrated Soup & Sauces from HACO AG

BRAND OWNER CHALLENGE

Handling resistance



Dehydrated
Soup & Sauces
from HACO AG

Solution

- Metallyte™ 18MM883 film was chosen for its excellent oxygen and moisture barrier properties, essential characteristics for packaging dehydrated soups & sauces with a shelf-life of 18 months
 - previous structure: Paper//Alu 7//PE
 - new structure: Paper//18MM883 film//PE
- Metallyte™ 18MM883 film is used as the middle ply of the lamination, enhancing the handling resistance of the package and improving the converting process



Features

- Excellent light, oxygen and moisture barrier
- Excellent puncture and flex-crack resistance
- Treated on the non-metal side for adhesive laminations

Benefits

- Improved handling resistance:
 - less "shop-worn" appearance
 - improved puncture resistance
- Cost-effectiveness
- Much improved life cycle inventory (LCI) / environmental performance by replacing aluminum foil with metallized OPP

Contact your Jindal Films representative for more information

www.jindalfilms.com - info@jindalfilms.com

© 2018 Jindal Films. Jindal Films, the Jindal Films' logo, and other product or service names used herein are trademarks of Jindal Films, unless indicated otherwise. You may not upload, display, publish, license, post, point to, frame, transmit or distribute either this document or its information, whether in whole or in part, without Jindal Films' prior written authorization. To the extent Jindal Films provides prior written authorization, the user may use the document or its information only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. Any data included herein may be based upon analyses of representative samples and not the actual product shipped, typical values, or otherwise. The information in this document relates solely to the named product or materials when not in combination with any other product or material(s). We base the information on data believed to be reliable, but we do not represent, warrant or otherwise guarantee the accuracy, reliability, or completeness of this information. We do not expressly or implicitly warrant the merchantability, fitness for a particular purpose, or non-infringement, or suitability of the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of, or related to, anyone using or relying on any of the information in this document. This document is not an endorsement of any non-Jindal Films' product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "Jindal Films" and "Jindal" are each used for convenience, and may include Films Americas LLC, Jindal Films Americas LLC, Films Europe S.r.l., Jindal Films Virtón SPRL, Jindal Films India Ltd., or any companies affiliated with them in the production and sale of film products. There are a number of such affiliated companies, some with names including "Jindal" or "Films" and some not. Neither these terms and conditions, nor anything else in this document, is intended to override or supersede the legal separateness of those affiliated companies and responsibility for local action and accountability remains with them.

Jindal
Films