

Enhanced packaging performance through Metallyte™ OPP film

Metallyte™ 28UBWES film is an ultra-high barrier, metallized, white opaque sealable polypropylene film.

FILM TYPE

Metallyte™ 28UBWES metallized, cavitated white OPP film

FORMAT

Horizontal form fill seal (HFFS) flow-pack

MARKET SEGMENT

Home & personal care

APPLICATION

“Aquasure” water purification tablets from Eurotab

BRAND OWNER CHALLENGE

Seal integrity and high barrier requirements



Aquasure tablets
from Eurotab

Solution

- Metallyte™ 28UBWES film has been selected for this novel application due to its advantages over aluminum-based laminates. The product is a compressed powder tablet used in mobile water treatment units to clarify and purify water
- Metallyte™ 28UBWES film was chosen for its excellent moisture barrier properties and high seal integrity, essential characteristics for packaging in lamination to PET very hygroscopic substances
- Metallyte™ 28UBWES film retains its barrier, withstanding extended distribution and difficult end use environments. Unlike foil laminates, it is not susceptible to compromised barrier from pin-holing and flex-cracking as a result of handling



Features

- Excellent light, oxygen and moisture barrier
- Puncture and flex-crack resistance
- Exceptional seal strength
- White opaque appearance on sealant side

Benefits

- High seal integrity
- High barrier to humidity
- Puncture resistance

Contact your Jindal Films representative for more information
www.jindalfilms.com - info@jindalfilms.com

Jindal
Films

© 2018 Jindal Films. Jindal Films, Jindal Films, the Jindal Films logo, and other product or service names used herein are trademarks of Jindal Films, unless indicated otherwise. You may not upload, display, publish, license, post, point to, frame, transmit or distribute either this document or its information, whether in whole or in part, without Jindal Films' prior written authorization. To the extent Jindal Films provides prior written authorization, the user may use the document or its information only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. Any data included herein may be based upon: analyses of representative samples and not the actual product shipped, typical values, or otherwise. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We base the information on data believed to be reliable, but we do not represent, warrant, or otherwise guarantee the accuracy, reliability, or completeness of this information; nor do we warrant, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, or suitability of the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of, or related to, anyone using or relying on any of the information in this document. This document is not an endorsement of any non-Jindal Films' product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "Jindal Films" and "Jindal" are each used for convenience, and may include Films Americas LLC, Jindal Films Americas LLC, Films Europe S.à.r.l., Jindal Films Virton SPRL, Jindal Films India Ltd., or any companies affiliated with them in the production and sale of film products. There are a number of such affiliated companies, some with names including "Jindal" or "Films" and some not. Neither these terms and conditions, nor anything else in this document, is intended to override or supersede the legal separateness of those affiliated companies and responsibility for local action and accountability remains with them.