

Label-Lyte™ films for wrap-around, reel-fed label applications

Jindal

Films

Label-Lyte™ wrap-around, reel-fed oriented polypropylene (OPP) films make up a large sub-family of materials specially designed for beverage container labeling. Transparent, white and metalized grades are available. The films offer outstanding product presentation and controlled mechanical properties for ease of application.

Printer benefits

- printability - good receptivity to most inks and very good print definition
- registration - high film modulus in machine direction for good print registration control

Brand owner benefits

- appearance - excellent film transparency (clear films) or opacity (cavitation technology for white films)
- film performance - high modulus in machine direction ensures low film stretchability
- high yield (cavitated opaque films) - lower density of cavitated films means lighter rolls with associated benefits of lower transportation and storage costs
- hot melt anchorage - selected, specially engineered films provide strong and stable bonds
- efficiency - ideal for high-speed labeling
- PET bottle recycling - Label-Lyte films' polymer density aids flotation separation from PET bottles and also means there is typically less resulting waste, by weight, than with other materials.



Benefits

- **reliable, consistent label converting**
- **outstanding optical properties**
- **alternatives for design, efficiency, and cost savings**
- **high speed labeling performance**



Label-Lyte™
films

Europe,
Middle East, Africa
& Asia Pacific portfolio

Label-Lyte™ wrap-around, reel-fed films are designed for use as single web applications or as laminates.

Grade	Type	Structure*	μ	g/m ²	Description
33LL247	White		33	20.5	Cavitated (density 0.62) super white, one-side-treated, for lamination with LL222 or LL666.
38LL247 47LL247	White		38 47	23.6 29	Cavitated (density 0.62) super white, one-side-treated, for single web applications. 38μ film is slip controlled.
33DL247 38DL247	White		33 38	17.7 20.5	Cavitated (density 0.54) super white, one-side-treated, for single web applications. High yield, less waste, same performance. Slip controlled.
35LH247 40LH247	White		35 40	25.4 29	Cavitated (density 0.73) one-side-treated, for single web applications. High stiffness, low creasing.
38LW280	Metalized white		38	23.6	Metalized film for single web applications. Slip controlled.
30LL666 35LL666 40LL666	Clear		30 35 30	28.2 31.8 37.3	High transparency, glossy films for single web applications. Slip controlled.
35LL400	Clear		35	31.9	High transparency film for single web applications. One-side-treated.
17LL222	Clear		17	15.5	High transparency and glossy one-side-treated overlaminating film.

* Film structure color legend

Clear polymer	White opaque	Uncoated skin	Acrylic coating	Matte static controlled coating	Static controlled coating	Top coated printable coating	Adhesive receptive coating	Engineered printing surface	Metalized
---------------	--------------	---------------	-----------------	---------------------------------	---------------------------	------------------------------	----------------------------	-----------------------------	-----------

** Values are representative of film thickness; actual thickness may vary, see product data sheet for actual values.
Not all film types are available in all countries. Please contact your local Jindal Films sales representative to confirm availability.

Contact your Jindal Films representative
for more information

www.oppfilms.com

Jindal
Films

© 2013 Jindal Films. Jindal Films, the Jindal Films logo, and other product or service names used herein are trademarks of Jindal Films, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without Jindal Films' prior written authorization. To the extent Jindal Films authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to, or reproduce it in whole or in part on, a website. Jindal Films does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee the accuracy, reliability, or completeness of this information; nor do we warrant, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, or suitability of the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of, or related to, anyone using or relying on any of the information in this document. This document is not an endorsement of any non-Jindal Films' product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "Jindal Films" and "Jindal" are each used for convenience, and may include Films Americas LLC, Jindal Films Americas LLC, Films Europe S.A.R.L. or any companies affiliated with them in the production and sale of film products. There are a number of such affiliated companies, many with names including "Jindal" or "Films". Neither the use of these terms of convenience, nor anything else in this document, is intended to override or supersede the legal separateness of those affiliated companies and responsibility for local action and accountability remains with them.